

XXIV PHYSICS IN COLLISION - Boston, June 27-29, 2004

THE MiniBooNE EXPERIMENT

Alexis Aguilar-Arevalo for the MiniBooNE collaboration
Department of Physics, Columbia University,
512 West 120th St., New York, NY, 10025, USA

ABSTRACT

MiniBooNE is an experiment designed to provide a definitive test for the $\bar{\nu}_\mu \rightarrow \bar{\nu}_e$ oscillations signal seen by LSND. Here, a brief summary of the MiniBooNE goals and strategies is presented, as well as some highlights of its current status.

1 Introduction

The LSND oscillations signal [1] (event excess of 3.8σ significance) requires a squared neutrino mass difference of the order of $0.3 - 3 \text{ eV}^2$. This is inconsistent with the three neutrino picture of the Standard Model (SM) when the oscillation evidence from solar and atmospheric neutrinos [4] is taken into account. MiniBooNE's primary goal is to confirm or refute the oscillations interpretation of the LSND $\bar{\nu}_e$ excess.

2 MiniBooNE neutrinos and detector overview

The neutrino beam ¹ is produced from the decay of charged mesons that are created when protons from the Fermilab Booster (8.0 GeV kinetic energy) impact a 1.7 interaction length Be target. The target is placed inside a focusing horn whose polarity can be set to run in either ν or $\bar{\nu}$ mode. Currently the experiment runs in

¹For more details see Ref.[2] and references therein

ν mode, and the horn increases the neutrino flux at the detector by a factor of ~ 5 . The detector is a 12 m diameter sphere filled with mineral oil (hydrocarbon chain). Its interior is covered ² by 1280 PMT's that gather the light produced by processes inside the tank. It is surrounded by an optically isolated veto region designed to tag cosmic rays with 240 PMT's . The transparent medium of the oil makes it primarily a Cerenkov detector, although an important component of scintillation light is present in any occurring process. The charge and time response of the tank PMT's is monitored continuously with a laser system. The energy scale of electron-type events is calibrated using the spectrum of Michel electrons. We use cosmic ray muons to determine the energy scale for muon-type events. The positions and angles of the incoming cosmic rays are measured with a tracking hodoscope situated above the detector and the stopping point is determined with a system of 7 scintillating cubes located throughout the detector.

3 Analysis status

MiniBooNE is presently studying ³ three processes that will be used to tune the detector Monte Carlo and the reconstruction algorithms: ν_μ charged current quasi-elastic (CCQE) events which will be used to determine the incoming neutrino flux; neutral current (NC) π^0 production which will account for the largest ν_μ misidentification background to the oscillation signal; and NC ν_μ elastic scattering which can be used to study the optical properties of the oil. The $\nu_\mu \rightarrow \nu_e$ oscillation analysis is a blind analysis and, as such, we have not yet looked for ν_e events. However, recent studies [2] show that with 1×10^{21} protons on target (P.O.T.) approximately 300 signal events are expected for LSND-like oscillations, as well as about 434 misidentified ν_μ interactions (dominated by ~ 294 NC π^0 production), and about 346 intrinsic ν_e background events. Figure 1 shows the updated sensitivity and measurement capability for this number of protons.

4 Conclusion

The MiniBooNE experiment can definitively confirm or refute the LSND oscillation signal with 1×10^{21} P.O.T. Currently, 30% of this amount has been collected. The collaboration is presently working on the analysis of ν_μ CCQE, NC π^0 's and NC elastic scattering. The $\nu_\mu \rightarrow \nu_e$ analysis is expected to produce first results in 2005.

²10% photocathode coverage.

³For a detailed analysis update see Ref.[3]. Plots shown in the poster are included therein.




Figure 1: *Left: MiniBooNE $\nu_\mu \rightarrow \nu_e$ oscillation sensitivity at 90% C.L., 3σ , and 5σ compared to the LSND allowed region. Right: MiniBooNE $\nu_\mu \rightarrow \nu_e$ parameter measurement capability at 1σ and 2σ for high and low Δm^2 .*

5 Acknowledgements

This work is supported by the National Science Foundation and the Department of Energy. The presenter of this poster was supported by NSF grant PHY-98-13383.

References

1. A. Aguilar, *et al.*, Phys. Rev. **D64** 112007 (2001).
2. The MiniBooNE Run Plan: <http://www-boone.fnal.gov/publicpages/>, Nov. 2003.
3. S.J. Brice, The MiniBooNE experiment, in Proc. Neutrino 2004, Paris, June 2004.
4. R. Davis, Prog. Part. Nucl. Phys. **32**, 13 (1994); P.N. Anselmani, *et al.*, Phys. Lett. **B328**, 377 (1994); J.Yoo, *et al.* [Super-Kamiokande Collab.], Phys. Rev. **D68**, 092002 (2003); Q.R. Ahmad, *et al.* [SNO Collab.], Phys. Rev. Lett. **89**, 011302 (2002); K. Eguchi, *et al.*, [KamLAND Collab.], Phys. Rev. Lett. **90**, 02182 (2003). Y. Hirata, *et al.*, Phys. Lett **B335**, 237 (1994); Y. Totsuka, Nucl. Phys. **A663**, 218 (2000); Y. Fukuda, *et al.* Phys. Rev. Lett. **81**, 1562 (1998); T. Toshito, *et al.* [Super-Kamiokande Collab.], arXiv:hep-ex/0105023; M.H. Ahn, *et al.* [K2K Collab.], Phys. Rev. Lett. **90**, 041801 (2003).